


Grade 8 USS Flat Washers



Nominal Size or Basic Bolt Diameter	A			B			C	
	Inside Diameter (Inches)			Outside Diameter (Inches)			Thickness (Inches)	
	Basic	Tolerance		Basic	Tolerance		Tolerance	
		+	-		+	-	Max	Min
1/4"	0.312	0.015	0.005	0.734	0.015	0.007	0.065	0.055
5/16"	0.375	0.015	0.005	0.875	0.030	0.007	0.080	0.064
3/8"	0.438	0.015	0.005	1.000	0.030	0.007	0.080	0.064
7/16"	0.500	0.015	0.005	1.250	0.030	0.007	0.080	0.064
1/2"	0.562	0.015	0.005	1.375	0.030	0.007	0.116	0.100
9/16"	0.625	0.015	0.005	1.469	0.030	0.007	0.116	0.100
5/8"	0.688	0.030	0.007	1.750	0.030	0.007	0.138	0.122
3/4"	0.812	0.030	0.007	2.000	0.030	0.007	0.138	0.122
7/8"	0.938	0.030	0.007	2.250	0.030	0.007	0.160	0.136
1"	1.062	0.030	0.007	2.500	0.030	0.007	0.160	0.136

Material: 1035 Steel or Better (Grade 8 Equivalent)
Hardness: 38-45HRC
Mechanical & Physical Properties: ASTM F-436 - USS Pattern

440.606.6557

www.boltsandnuts.com

info@boltsandnuts.com

ONLINE FASTENER GROUP LLC CLAIMS ALL PROPRIETARY RIGHTS TO THIS DRAWING AND THE INFORMATION IT CONTAINS. THIS MATERIAL IS CONFIDENTIAL. DISCLOSURE, REPRODUCTION, AND MANUFACTURING IS STRICTLY PROHIBITED WITHOUT THE EXPRESS WRITTEN PERMISSION OF ONLINE FASTENER GROUP LLC. ALL RIGHTS OF DESIGN OR INVENTION ARE RESERVED.