




## Steel Heavy Hex Nuts



| Nominal Size<br>or Basic Bolt<br>Diameter | F                       |       | H                  |       |
|---|-------------------------|-------|--------------------|-------|
|   | Width Across Flats (IN) |       | Nut Thickness (IN) |       |
|   | Max                     | Min   | Max                | Min   |
| 1/4"                                      | 0.500                   | 0.488 | 0.250              | 0.218 |
| 5/16"                                     | 0.562                   | 0.546 | 0.314              | 0.280 |
| 3/8"                                      | 0.688                   | 0.669 | 0.377              | 0.341 |
| 7/16"                                     | 0.750                   | 0.728 | 0.441              | 0.403 |
| 1/2"                                      | 0.875                   | 0.750 | 0.504              | 0.464 |
| 5/8"                                      | 1.062                   | 1.031 | 0.631              | 0.587 |
| 3/4"                                      | 1.250                   | 1.212 | 0.758              | 0.710 |
| 7/8"                                      | 1.438                   | 1.394 | 0.885              | 0.833 |
| 1"  | 1.625                   | 1.575 | 1.012              | 0.956 |

**Dimensions: ASME B18.2.2**  
**Material: Low Carbon Steel**  
**Threading: ASME B1.1, UNC & UNF**

440.606.6557

www.boltsandnuts.com

info@boltsandnuts.com

ONLINE FASTENER GROUP LLC CLAIMS ALL PROPRIETARY RIGHTS TO THIS DRAWING AND THE INFORMATION IT CONTAINS. THIS MATERIAL IS CONFIDENTIAL. DISCLOSURE, REPRODUCTION, AND MANUFACTURING IS STRICTLY PROHIBITED WITHOUT THE EXPRESS WRITTEN PERMISSION OF ONLINE FASTENER GROUP LLC . ALL RIGHTS OF DESIGN OR INVENTION ARE RESERVED.