




## Stainless Steel Hex Head Cap Screws



Nominal Size or Basic Bolt Diameter	A		C		D		LT
	Width Across Flats		Height of Head		Full Size Body Diameter		
	Max	Min	Max	Min	Max	Min	
1/4"	0.438	0.428	0.163	0.150	0.2500	0.2450	1-1/4" and Longer
5/16"	0.500	0.489	0.211	0.195	0.3125	0.3065	1-1/2" and Longer
3/8"	0.562	0.551	0.243	0.226	0.3750	0.3690	1-1/2" and Longer
7/16"	0.625	0.612	0.291	0.272	0.4375	0.4305	1-3/4" and Longer
1/2"	0.750	0.736	0.323	0.302	0.5000	0.4930	2" and Longer
9/16"	0.812	0.798	0.371	0.348	0.5625	0.5545	2-1/4" and Longer
5/8"	0.938	0.922	0.403	0.378	0.6250	0.6170	2-1/4" and Longer
3/4"	1.125	1.100	0.483	0.455	0.7500	0.7410	2-3/4" and Longer
7/8"	1.312	1.285	0.563	0.531	0.8750	0.8660	3" and Longer
1"	1.500	1.469	0.627	0.591	1.0000	0.9900	3-1/4" and Longer

**Dimensions: ASME B18.2.1**  
**Material: 18-8 (T304) Stainless Steel**  
**Threading: ASME B1.1, UNC & UNF, Class 2A**

440.606.6557

www.boltsandnuts.com

info@boltsandnuts.com

ONLINE FASTENER GROUP LLC CLAIMS ALL PROPRIETARY RIGHTS TO THIS DRAWING AND THE INFORMATION IT CONTAINS. THIS MATERIAL IS CONFIDENTIAL. DISCLOSURE, REPRODUCTION, AND MANUFACTURING IS STRICTLY PROHIBITED WITHOUT THE EXPRESS WRITTEN PERMISSION OF ONLINE FASTENER GROUP LLC. ALL RIGHTS OF DESIGN OR INVENTION ARE RESERVED.