




Slotted Truss Head Machine Screws



Nominal Size or Basic Bolt Diameter	A		H		M
	Head Diameter		Height of Head		Slot Width
	Max	Min	Max	Min	Min
#6	0.321	0.303	0.086	0.074	0.039
#8	0.384	0.364	0.102	0.088	0.045
#10	0.448	0.425	0.118	0.103	0.050
#12	0.511	0.487	0.134	0.118	0.056
1/4"	0.573	0.546	0.150	0.133	0.064
5/16"	0.698	0.666	0.183	0.162	0.072

Dimensions: ASME B18.6.3 - Full Thread
Material: Carbon Steel
Threading: ASME B1.1, UNC & UNF, Class 2A

440.606.6557

www.boltsandnuts.com

info@boltsandnuts.com

ONLINE FASTENER GROUP LLC CLAIMS ALL PROPRIETARY RIGHTS TO THIS DRAWING AND THE INFORMATION IT CONTAINS. THIS MATERIAL IS CONFIDENTIAL. DISCLOSURE, REPRODUCTION, AND MANUFACTURING IS STRICTLY PROHIBITED WITHOUT THE EXPRESS WRITTEN PERMISSION OF ONLINE FASTENER GROUP LLC. ALL RIGHTS OF DESIGN OR INVENTION ARE RESERVED.