BOLTS AND NUTS .COM					St	ainles	ss Stee	el Hex Head Cap Screv	vs
		A2-70							
	Nominal	A		с		D		LT	
	Size or Basic Bolt Diameter	Width Across Flats (mm)		Height of Head (mm)		Full Size Body Diameter (mm)		Product will be Partial Thread if the	
		Max	Min	Мах	Min	Max	Min	Length ("L") is	
	M6	10	9.78	4.15	3.85	6	5.82	30mm and Longer	
	M8	13	12.73	5.45	5.15	8	7.78	35mm and Longer	
	M10	17	16.73	6.58	6.22	10	9.78	40mm and Longer	
	M12 M14	19 22	18.67	7.68 8.98	7.32 8.62	12 14	11.73 13.70	40mm and Longer 50mm and Longer	
	M14 M16	22	21.70 23.67	10.18	9.82	14	15.70	50mm and Longer	
Dimensions: Full Thread DIN 933   Partial Thread DIN 931 Material: A2-70 Stainless Steel per ISO 3506 Part 1 Tensile Strength: 700 MPa Minimum Headmark: "A2-70" and MFG ID									
440.606.6557				www.boltsandnuts.com				info@boltsandnuts.com	
L ONLINE FASTENER GROUP LLC CLAIMS ALL PROPRIETARY RIGHTS TO THIS DRAWING AND THE INFORMATION IT CONTAINS. THIS MATERIAL IS CONFIDENTIAL. DISCLOSURE, REPRODUCTION, AND MANUFACTURING IS STRICTLY PROHIBITED WITHOUT THE EXPRESS WRITTEN PERMISSION OF ONLINE FASTENER GROUP LLC . ALL RIGHTS OF DESIGN OR INVENTION ARE RESERVED.									